



SHAANXI TONLY HEAVY INDUSTRIES CO.,LTD.

Address: No.2339, Fengchan Road, Fengdong new city, Xi'an City Shaanxi Province, China. Sales Hotline:+86-029-38001214 Fax:+86-029-38001213

Shaanxi Tonly Heavy Industries Co.,Ltd,reserves the right of design changes and internetation. A parameters and details are subject to the commercial contract and vehicles.



TONLY TLD65

OFF ROAD DUMP TRUCK


PAYLOAD: CARGO CAPACITY: Struck 25m³/2:1 Heaped 30.6m³ **ENGINE:** 430HP/316KW






Inventor and Leader of China Off-road Dump Truck





Cargo body

In line with the characteristics of material, the steel plate with wear-resisting.



suspension

Leaf spring balance rear suspension, adapts the off-road working condition. Upper & lower double V type guide structure with more load and high reliability.



Tire

Special mining tire for mine only with longitudinal and transverse groove design, which provide excellent grip performance and comfort of operation strong carrying capacity and long service life.



Intake system

Three stage combined air filter can improve the efficiency of air filtering, and improve the air clearness.



Steering system

Tonly developed full hydraulic steering system (TONLY owns all patent of this technology), reduce the steering oil temperature, steering operation is lighter, greatly improve the life cycle of the system components, and ensure the truck safety.



FOPS/ROPS Certificate

Tonly product is the only one obtained the certificate for big payload through severe test



• Through beam structure

Anti-collision beam + bumper + through beam structure, effectively protects the driver and the



Hydraulic Retarder

Transmission combined with hydraulic retarder can reduce the speed of the truck when going down a long slope, works long time and high power ,reduce the wear out of braking components and extend the tire life time, ensure the operation safety.

China Off-road Dump Truck Standard-setter





TONLY TLD65 Configurations and Characteristics



Engine

WEICHAI (Tier III) engine with stable performance, reliable quality, fuel conservation and environment protection.




Axle Assembly

TONLY and HANDE jointly design the special axle for mine transportation. Strengthened single casting axle housing, double reduction. Big torque, high transmission efficiency and high reliability.



Transmission

FC6A210p® automatic control transmission, high reliability, convenient operation, high efficiency, excellent acceleration performance.



• Main frame

High-strength steel plate is used for flexible chassis frame for mine, which has national patent. The impact abrasion is strong with long service life.



• Lifting Device

HYVA hydraulic lifting system, strong lifting power, stable lifting performance.

Sales Championship for consecutive 16 years



TONLY TLD65 Technical Parameter

| Complete technical parameter | |
|--------------------------------------|--|
| Model | TLD65 Off-Road Dump Truck |
| Brand | TONLY |
| Manufacturer | Shaanxi TONLY Heavy Industries Co.,Ltd. |
| Drive mode | 6×4 |
| GVW (t) | 65 |
| Rated loading capacity (t) | 40 |
| Kerb mass (t) | 25 |
| Overall dimension | 8895X3220X3800mm |
| Minimum turning radius | 10.5m |
| Wheelbase | 3600+1500mm |
| Wheel tread | 2442mm/2252mm |
| Minimum ground clearance | 355mm |
| Maximum height of lifting cargo body | 7650mm |
| Maximum angel of lifting cargo body | 53° |
| Loading height | 3550mm |
| Brake distance | <12m (V=30km/h) |
| Maximum gradeability | 36% |
| Maximum speed | 42km/h |
| Engine | |
| Model | WP12G430 |
| Manufacturer/Country | WEICHAI/China |
| Total Horse power(HP/KW) | 430hp (316KW) |
| Transmission | |
| Model | FC6A210 (Automatic) |
| Manufacturer/Country | Xi'an FC Intelligent Transmission Co., Ltd. /China |
| Axle | |
| Model | 13t steering front axle, 2x25t drive middle and rear axl |
| Manufacturer/Country | Shaanxi Hande Axle Co., Ltd./China |
| Tire/Rim | |
| Tire Model | 14.00R25 |
| Rim size | 10.00-25 |
| Container | |
| Bottom plate material / thickness | T700/16mm |
| Rear plate material / thickness | T700/10mm |
| Front plate material / thickness | T700/10mm |
| Side plate material / thickness | T700/10mm |
| Loading volume | Struck 25m³/2:1 Heaped 30.6m³ |
| Loading volume (Coal body) | |

| Hydraulic system | |
|-----------------------------|---|
| Model | HYVA 179 |
| Manufacturer/Country | HYVA Machinery (Yangzhou) Co., Ltd./China |
| Steering gear | Double Steering |
| Lifting time for cargo body | 21s |
| Falling time for cargo body | 21s |
| Weight distribution | |
| Empty payload | |
| Front axle | 9000kg |
| Rear axle | 16000kg |
| Total weight(50% fuel) | 25000kg |
| Heavy payload | |
| Front axle | 14000kg |
| Rear axle | 51000kg |
| Total weight | 65000kg |

